


REFERENCE SPECIFICATIONS

	SHEET		TILE			
	FLOR-EVER PLUS		CHOICES	ALTERNATIVES	TT SERIES	CX SERIES
Approx.Installed Cost Per Square Foot	\$3.00 - \$3.50		\$1.50 - \$2.00		\$1.35 - \$2.00	\$1.35 - \$2.00
Colors Available	20		6	46	7	4
Width	12 ft.		12" x 12" (305mm x 305mm)			
Length	Up to 120'		—			
Gauge – Overall	.080" nominal (2.03mm)		1/8" (3.2mm)	3/32" (2.4mm)	.100" (2.5mm)	
Vinyl Composition Wearlayer	—		—	—	—	
Vinyl Wearlayer	.020"(.51mm)		—	—	—	
Packing	—		45 pcs. (45 sq. ft.; 4.2 sq. meters)			
REFERENCE SPECIFICATIONS • ASTM F 1303	Type I, Grade 1 Class A backing		—			
• ASTM F 1066	—		Class 2			Class 2***
FIRE TEST DATA • ASTM E 648; NFPA-253; Critical Radiant Flux - 0.45 watts/cm ² or greater			YES			
• ASTM E 662; NFPA-258; NBS Smoke Density - 450 or less			YES			
• D.O.T. Motor Vehicle Safety Standard 302	YES		—			
FloorScore Certified for Indoor Air Quality Performance			YES*			
Static Load Limit	175 psi		250 psi			
HUD/FHA Minimum Property Standards			YES			YES***
Recommended Subfloor	Suspended wood, concrete, all grade levels					
Installation Method	Full Spread					
Recommended Congoleum Adhesive	3044		AD42			
Seam Sealer	SU80 or SU92 Seam Sealer		—			
Warranty	Five-Year Commercial Limited Warranty					
Durability	Excellent					
Ease of Maintenance	Excellent					

* FloorScore certified hard surface flooring products are an alternative compliance to LEED credit EQ4.3 Low-Emitting Materials: Flooring Systems.

** Modified ASTM F 970

***When .100" gauge is specified.