



PRODUCT:		DURACERAMIC DIMENSIONS
Construction:	Wear Surface:	Nano-composite Surface glaze fortified with Nylon and Aluminum Oxide featuring Silver Antibacterial Product Protection and Scotchgard™ Protector
	Base:	Limestone composite
Nominal Overall Gauge:		0.160" (4.1 mm)
Nominal Tile Size:		12" x 24"
Packaging:		20 Sq. Ft. per Carton
Pieces per Carton:		10
Shipping Weight per Package:		36 lbs. per Carton
Passes NBS Smoke Density:		Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm²):		Yes
Passes Motor Vehicle FMVSS 302:		Yes
PEI Rating:		3-4
Static Load Limit:		250 psi
Slip Resistance:		Meets ADA Recommendations
FloorScore Certified:		Yes
Warranty Coverage:		Lifelong Residential
Additional Scotchgard™ Protector		
Will be easy to clean		15 Years
Will repel dirt and grime		15 Years
		5 Year Light Commercial
Installation Method:		Fully Adhered or Floating Installation over UnderFlor
Subfloor Application:		On, above or below grade level
Adhesive:		Congoleum DS-100 DuraSet Adhesive
Adhesive Coverage:		
Fully adhered:		200 to 250 sq. ft. per gallon
Recommended Trowel:		1/16" wide x 1/32" deep x 1/32" apart
Grout:		Congoleum DuraCeramic Premixed Grout
Joint Sealer (Recommended for ungrouted floors):		Congoleum DS200 DuraCeramic Joint Sealer
Suggested Usage:		
Light Commercial		Yes
Private Residential		Yes
Finished product manufactured in the United States		