



7/23/13

PRODUCT:	STRUCTURE PLANK Pioneer & Trek
Construction:	High Performance Urethane fortified with Aluminum Oxide
Wear Surface:	Vinyl composition
Base:	Micro Bevel Edge
Edge Appearance:	
Nominal Overall Gauge:	0.120" (3.0 mm)
Nominal Wearlayer Gauge:	0.020" (0.5 mm)
Nominal Plank Size:	7.25" x 48"
Packaging:	36.25 square feet per carton 15 pieces per carton
Shipping Weight per Package:	42 lbs. per Carton
Applicable Specifications:	ASTM F1700, Cl. 3
Static Load Limit:	250 psi
Slip Resistance:	Meets ADA Recommendations
FloorScore Certified:	Yes
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm²):	Yes
Warranty Coverage:	Lifelong Limited Residential Warranty 10 Years Commercial Limited Warranty
Installation Method:	Fully Adhered
Subfloor Application:	On, above or below grade level
Adhesive:	
	Congoleum AD-32 Pressure Sensitive adhesive for: Residential and Light Commercial application over All Approved Substrates Trowel Size: 1/16" wide, 1/32" deep, 1/32" apart U notch Adhesive Coverage: 200 to 250 sq. ft. per gallon
	Congoleum AD-62 Wet Set Adhesive for: Commercial application over Approved Substrates Trowel Size Porous Surface: 1/16" wide, 1/16" deep, 1/16" apart square notch Adhesive Coverage: 125 to 150 sq. ft. per gallon Trowel Size Non-Porous Surface: 1/32" wide, 1/16" deep, 1/32" apart U notch Adhesive Coverage: 185 to 245 sq. ft. per gallon
Suggested Usage:	
Public Commercial	Yes
Light Commercial	Yes
Private Residential	Yes