



7/23/13

PRODUCT:	STRUCTURE TILE Terra Nova & Crete
Construction:	High Performance Urethane fortified with Aluminum Oxide
Wear Surface:	Vinyl composition
Base:	Square Edge
Edge Appearance:	
Nominal Overall Gauge:	0.120" (3.0 mm)
Nominal Wearlayer Gauge:	0.020" (0.5 mm)
Nominal Plank Size:	18" x 18"
Packaging:	36 square feet per carton 16 pieces per carton
Shipping Weight per Package:	42 lbs. per Carton
Static Load Limit:	250 psi
Applicable Specifications:	ASTM F1700, Cl. 3
Slip Resistance:	Meets ADA Recommendations
FloorScore Certified:	Yes
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm²):	Yes
Warranty Coverage:	Lifelong Limited Residential Warranty 10 Years Commercial Limited Warranty
Installation Method:	Fully Adhered
Subfloor Application:	On, above or below grade level
Adhesive:	
Congoleum AD-32 Pressure Sensitive adhesive for:	
Residential and Light Commercial application over All Approved Substrates	
Trowel Size:	1/16" wide, 1/32" deep, 1/32" apart U notch
Adhesive Coverage:	200 to 250 sq. ft. per gallon
Congoleum AD-62 Wet Set Adhesive for:	
Commercial application over Approved Substrates	
Trowel Size Porous Surface:	1/16" wide, 1/16" deep, 1/16" apart square notch
Adhesive Coverage:	125 to 150 sq. ft. per gallon
Trowel Size Non-Porous Surface:	1/32" wide, 1/16" deep, 1/32" apart U notch
Adhesive Coverage:	185 to 245 sq. ft. per gallon
Suggested Usage:	
Public Commercial	Yes
Light Commercial	Yes
Private Residential	Yes