Revised 01-15-13

PRODUCT:	AirStep Advantage UltraTec Construction
Construction: Wearlayer:	Vinyl Resin and Urethane, Reinforced with Aluminum Oxide featuring Scotchgard Protection and Silver for Antibacterial Product Protection
Cushion:	High Density Vinyl Foam
Backing:	Fibrous Felt Inner Layer and Dense Flexible Vinyl Composite Backing
Applicable Specifications:	ASTM, F1303, Type I, Gr. 2, Class B
FloorScore Certified:	Yes
Meets or Exceeds FHA / HUD Minimum Property Standards:	Yes
Width:	12 Feet
Packaging:	80-150 S.Y.
Shipping Weight per Unit:	4.75 lbs. per S.Y.
Shipping Weight per Package:	380-712 lbs. avg.
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm)^2:	Yes
Warranty Coverage:	AirStep Extended Lifelong Limited Warranty
Installation Method:	Your Choice Plus Loose, Perimeter or Fully Adhered over Approved Wood, Concrete, and Qualifying Existing Resilient Floors
Subfloor Application:	All grade levels
Adhesive:	Congoleum AS-01 AirStep Adhesive
Porous and Non-Porous Surfaces:	Applicator: ¼” Nap Paint Roller
Adhesive Coverage:	300 to 350 sq. ft per gallon
Optional Fully Adhere Application:	
Porous Surface Only:	Trowel Size: 1/16” wide, 1/32” deep, 1/32” apart
Adhesive Coverage:	200 to 250 sq. ft. per gallon
Seam Sealer:	Congoleum SU106 Seam Sealer Kit
Suggested Usage:	
Private Residential	Excellent

Finished product manufactured in the United States