



PRODUCT:	AirStep Basix UltraTec Construction
Construction:	Wearlayer: Scuff-resistance Matte Finish Urethane
	Cushion: High Density Vinyl Foam
	Backing: Fibrous Felt Inner Layer and Dense Flexible Vinyl Composite Backing
FloorScore Certified:	Yes
Width:	12 Feet
Packaging:	80-160 S.Y.
Shipping Weight per Unit:	3.06 lbs. per S.Y.
Shipping Weight per Package:	234-475 lbs. avg.
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm)²:	Yes
Warranty Coverage:	10-Year Limited Warranty
Installation Method:	Your Choice Plus Loose, Perimeter or Fully Adhered over Approved Wood, Concrete, and Qualifying Existing Resilient Floors
Subfloor Application:	All grade levels
Adhesive:	Congoleum AS-01 AirStep Adhesive
Porous and Non-Porous Surfaces Adhesive Coverage	Applicator: ¼" Nap Paint Roller 300 to 350 sq. ft per gallon
Optional Fully Adhere Application Porous Surface Only Adhesive Coverage	Trowel Size: 1/16" wide, 1/32" deep, 1/32" apart 200 to 250 sq. ft. per gallon
Seam Sealer:	Congoleum SU106 Seam Sealer Kit
Suggested Usage: Private Residential	Excellent

Finished product manufactured in the United States