



<b>PRODUCT:</b>	<b>AirStep Evolution</b> UltraTec Construction
<b>Construction:</b>	<b>Wearlayer:</b> Vinyl Resin and Urethane, Reinforced with Aluminum Oxide featuring Scotchgard Protection and Silver for Antibacterial Product Protection
	<b>Cushion:</b> High Density Vinyl Foam
	<b>Backing:</b> Fibrous Felt Inner Layer and Dense Flexible Vinyl Composite Backing
<b>Applicable Specifications:</b>	ASTM, F1303, Type I, Gr. 3, Class B
<b>FloorScore Certified:</b>	Yes
<b>Meets or Exceeds FHA / HUD Minimum Property Standards:</b>	Yes
<b>Width:</b>	12 Feet
<b>Packaging:</b>	80-160 S.Y.
<b>Shipping Weight per Unit:</b>	4.0 lbs. per S.Y.
<b>Shipping Weight per Package:</b>	320-568 lbs. avg.
<b>Passes NBS Smoke Density:</b>	Yes
<b>Passes Critical Radiant Flux (ASTM E-648&gt;0.45w/cm)<sup>2</sup>:</b>	Yes
<b>Warranty Coverage:</b>	Lifetime Limited Residential Warranty
<b>Installation Method:</b>	Your Choice Plus Loose, Perimeter or Fully Adhered over Approved Wood, Concrete, and Qualifying Existing Resilient Floors
<b>Subfloor Application:</b>	All grade levels
<b>Adhesive:</b>	Congoleum AS-01 AirStep Adhesive
<b>Porous and Non-Porous Surfaces Adhesive Coverage</b>	Applicator: ¼" Nap Paint Roller 300 to 350 sq. ft per gallon
<b>Optional Fully adhere Application Porous Surface Only Adhesive Coverage</b>	Trowel Size: 1/16" wide, 1/32" deep, 1/32" apart 200 to 250 sq. ft. per gallon
<b>Seam Sealer:</b>	Congoleum SU106 Seam Sealer Kit Pre-treat Seam with 3M Abrasion Pad and Dowel
<b>Suggested Usage:</b> <b>Private Residential</b>	Excellent

**Finished product manufactured in the United States**