



PRODUCT:	ArmorCore ArmorGuard Construction
Construction:	Low Gloss Vinyl Resin Composition
Wearlayer:	High Density Vinyl Foam
Cushion:	White Shield Filled Fibrous Composition
Backing:	BAC STOP Protection
Applicable Specifications:	ASTM, F1303, Type I, Gr. 3, Class A
Indoor Air Quality:	FloorScore Certified CHPS 01350 Certified
National Green Building Standard ICC 700-2008:	Meets
LEED MR5.0 Regional Materials:	Meets Guidelines
LEED EQ4.3 Certified Low Emitting Product:	Meets Guidelines
LEED EQ4.1 Certified Low Emitting Adhesive:	Meets Guidelines
Meets or Exceeds FHA /HUD Minimum Property Standards:	Yes
Slip Resistance:	Meets ADA Recommendations
Width:	6 and 12 Feet
Packaging:	40-130 S.Y. (6') and 80-190 S.Y. (12')
Shipping Weight per Unit:	2.71 lbs. per S.Y.
Shipping Weight per Package:	257 lbs. avg. (6') and 481 lbs. avg. (12')
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm²):	Yes
Warranty Coverage:	ArmorCore 5 Year Residential Limited Warranty
Installation Method:	Your Choice Fully Adhere or Perimeter Adhere over Approved Wood, Concrete and Qualifying Existing Resilient Floors
Subfloor Application:	All grade levels
Adhesive:	Congoleum 3044
Adhesive Coverage: Fully adhered:	200 to 250 sq. ft. per gallon
Recommended Trowel:	1/16" wide, 1/32" deep, 1/32" apart
Seam Sealer:	Congoleum SU80 or SU92
Suggested Usage: Private Residential	Excellent

Finished product manufactured in the United States.