



PRODUCT:	QUIK STIK UNDERFLOR UNDERLAYMENT
Construction:	Face: Pre-applied Pressure Sensitive Adhesive
	Backing: White Shield Filled Fibrous Composition <i>(Install this side down)</i>
Gauge (nominal)	.027" (without the release liner)
Packaging:	
Large Roll Order Code:	QSUFL
Contents:	1 roll 56.25" wide x 60 lin. ft. (281.25 sq. ft.) plus 1 roll of tape (1.89" x 60 lin. ft.)
Carton Weight:	65 lbs.
Small Roll Order Code:	QSUSC
Contents:	1 roll 56.25" wide x 30 lineal feet (140.63 sq. ft.) plus 1 roll of tape (1.89" x 30 lin. ft.)
Carton Weight:	30 lbs.
FloorScore Certified:	Yes
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm)²:	Yes
Warranty Coverage:	One year for wear and manufacturing defects
Installation Method:	All-In-One Floating Underlayment with adhesive for Installation DuraCeramic, DuraCeramic Dimensions, Ovations, Endurance and Impact
Subfloor Application:	All grade levels with moisture vapor emissions not to exceed 5 lbs. or 80% RH
Suggested Usage:	
Private Residential	Excellent
Light Commercial	Not Recommended
Public Commercial	Not Recommended

Finished product manufactured in the United States