



Construction	Layered Vinyl Plank
Wearlayer	Urethane Finish
Overall Thickness	0.080" (2.0 mm)
Width/length	6" x 36" (152.4 mm x 914.4 mm)
Edge	Square
Pieces Per carton	24
Coverage per carton	36 sq. ft. (3.3 m ²)
Weight per carton	28 lbs. (12.9 kg.)
Cartons per pallet	66
Pallets per Container	20

ASTM F 1700 Properties and Performance Specifications

ASTM F2055-10 Squareness	Passes - maximum 0.010 in. (0.25mm)
ASTM F2055 Size and Tolerance	Passes - at ±0.016 in./lin. Ft. (0.4 mm/305 mm)
ASTM F386 Thickness	Passes - as specified ±0.005 in. (0.13 mm)
ASTM F137 Flexibility	Passes - 1-in. (25.4-mm mandrel, no crack or break)
ASTM F2199 Dimensional Stability	Passes – no greater than 0.020 in./lin. Ft. (0.51mm/305 mm)
ASTM F925 Resistance to Chemicals	Passes - no change
ASTM F1515 Resistance to Light	Passes - less than 8 avg., max
ASTM F1514 Resistance to Heat	Passes - less than 8 avg., max

Additional Properties and Performance Specifications

ASTM F970 Static Load Limit	Passes –250 psi
ASTM E648 Critical Radiant Flux	Passes - ≥.45 watts/cm ² , Class 1
ASTM E662 Smoke Density	Passes - < 450
Slip Resistance	ADA Compliant
Warranty	5 Year Limited Residential
Recommended Adhesives	Congoleum AD32 or DS100 Adhesive
Subfloor Application:	On, above or below grade level
HUD/FHA Minimum Property Standards	Meets Guidelines
Indoor Air Quality:	FloorScore Certified CHPS 01350 Certified
National Green Building Standard ICC 700-2008:	Meets 9016 Requirements
LEED EQ4.3 Certified Low Emitting Product:	Meets Guidelines
LEED EQ4.1 Certified Low Emitting Adhesive:	Meets Guidelines

For additional installation, maintenance, or technical information, visit our website at www.congoleum.com or contact our Technical Services Department at 1-800-274-3266.