



PRODUCT:

Construction: Wearlayer:

Cushion:

Backing:

Applicable Specifications:

Indoor Air Quality:

**National Green Building Standard
ICC 700-2008:**

LEED MR5.0 Regional Materials:

LEED EQ4.3 Certified Low Emitting Product:

LEED EQ4.1 Certified Low Emitting Adhesive:

Passes NBS Smoke Density:

**Passes Critical Radiant Flux
(ASTM E-648 > 0.45w/cm²):**

Meets or Exceeds FHA /HUD

Minimum Property Standards:

Slip Resistance:

Width:

Packaging:

Shipping Weight per Unit:

Shipping Weight per Package:

Warranty Coverage:

Installation Method:

Subfloor Application:

Adhesive:

Porous and Non-Porous Surfaces:

Adhesive Coverage:

Optional Fully Adhere Application:

Porous Surface Only:

Adhesive Coverage:

Seam Sealer:

Private Residential Suggested Usage:

AirStep Plus® with UltraTec Construction

Vinyl Resin and Urethane, featuring Scotchgard™ Protector and Silver

High Density Vinyl Foam

Fibrous Felt Inner Layer and Dense Flexible Vinyl Composite Backing

ASTM, F1303, Type I, Gr. 3, Class B

FloorScore Certified

CHPS 01350 Certified

Meets

Meets Guidelines

Meets Guidelines

Meets Guidelines

Yes

Yes

Yes

Meets ADA Recommendations

12 Feet

80-160 S.Y.

3.2 lbs. per S.Y.

256-512 lbs. avg.

AirStep 20 Year Limited Warranty

15 Years - Scotchgard Protector

20 Years - Not to Curl, Open at seam, Buckle and not to release over joints in underlayment panels

Your Choice Plus

Fully Adhere, Perimeter Fasten or Loose Lay over Approved Wood, Concrete and Qualifying Existing Resilient Floors

All grade levels

UnderFlor® CR021 Adhesive or QS120 QuikStik Tape

Applicator: ¼" Nap Paint Roller

300 to 350 sq. ft per gallon

Trowel Size: 1/16" wide, 1/32" deep, 1/32" apart

200 to 250 sq. ft. per gallon

Congoleum SU106 Seam Sealer Kit (Abrade seams)

Excellent

Finished product manufactured in the United States