



PRODUCT:

Construction: **Wearlayer:**
Cushion:
Backing:

AirStep Plus® with UltraTec Construction

Vinyl Resin and Urethane, with Stain Defense System®
High-Density Vinyl Foam
Fibrous Felt Inner Layer and Dense Flexible Vinyl
Composite Backing

Applicable Specifications:

ASTM F1303, Type I, Grade 3, Class B

Indoor Air Quality:

FloorScore Certified
CHPS 01350 Certified

**National Green Building Standard
ICC 700-2008:**

Meets

LEED MR 5.0 Regional Materials:

Meets guidelines

LEED EQ 4.3 Certified Low Emitting Product:

Meets guidelines

LEED EQ 4.1 Certified Low Emitting Adhesive:

Meets guidelines

Passes NBS Smoke Density:

Yes

**Passes Critical Radiant Flux
(ASTM E-648 > 0.45w/cm²):**

Yes

**Meets or Exceeds FHA /HUD
Minimum Property Standards:**

Yes

Slip Resistance:

Meets ADA recommendations

Width:

12 feet

Packaging:

70-160 S.Y.

Shipping Weight per Unit:

3.2 lbs. per S.Y.

Shipping Weight per Package:

406 lbs. avg.

Warranty Coverage:

AirStep Plus 20 year residential limited
warranty including 20 year no buckle warranty

Installation Method:

Fully adhere, perimeter fasten, or loose lay over
approved wood, concrete and qualifying existing
resilient floors

Subfloor Application:

All grade levels

Adhesive:

UnderFlor® CR021 pressure-sensitive adhesive

Adhesive Coverage:

¼" nap paint roller, 300-350 sq. ft. per gallon,
for dry-set over porous or non-porous substrates

Trowel: 1/16" wide x 1/32" deep x 1/32" apart,
185-245 sq. ft. per gallon, for wet set over non-
porous substrates only

QuikStik Tape:

for perimeter-fasten install only

Seam Sealer:

Congoleum SU106

Recommended Usage:

Residential (including multifamily)

Finished product manufactured in the United States