



<b>Product:</b>	<b>ALTERNATIVES</b>
<b>Construction:</b>	Vinyl Composition (Polish required)
<b>Gauge (nominal):</b>	0.125" (1/8") (3.2mm)
<b>Size:</b>	12" X 12"
<b>Packaging:</b>	45 S.F./carton
<b>Shipping Weight per Package:</b>	64lbs. /carton
<b>Passes NBS Smoke Density:</b>	Yes
<b>Passes Critical Radiant Flux (ASTM E-648&gt;0.45w/cm2):</b>	Yes
<b>Static Load Limit:</b>	250 psi
<b>Slip Resistance:</b>	Meets ADA Recommendations
<b>FloorScore Certified:</b>	Yes
<b>Applicable Specifications:</b>	ASTM F1066, Cl. 2 MIL STD-1 623 D for Deck Covering
<b>Warranty Coverage:</b>	Ten Year (Residential) Five Year (Commercial)
<b>Installation Method:</b>	Fully Adhered
<b>Subfloor Application:</b>	On, above or below grade level
<b>Adhesive:</b>	UnderFlor® AD42 VCT Adhesive
<b>Adhesive Coverage:</b>	
<b>Fully adhered:</b>	250 to 300 sq. ft. per gallon
<b>Recommended Trowel:</b>	1/16" wide, 1/32" deep, 1/32" apart
<b>Suggested Usage:</b>	
<b>Public Commercial</b>	Excellent
<b>Light Commercial</b>	Excellent
<b>Private Residential</b>	Good

**Finished product manufactured in the United States**