



<b>PRODUCT:</b>	<b>ArmorCore Pro with UltraTec Construction</b>
<b>Construction:</b>	Matte Vinyl Resin Composition
<b>Wearlayer:</b>	High Density Vinyl Foam
<b>Cushion:</b>	Fibrous Felt Inner Layer and Dense Flexible Vinyl Composite Backing
<b>Backing:</b>	
<b>Applicable Specifications:</b>	ASTM, F1303, Type I, Gr. 3, Class B
<b>Indoor Air Quality:</b>	FloorScore Certified CHPS 01350 Certified
<b>National Green Building Standard ICC 700-2008:</b>	Meets
<b>LEED MR5.0 Regional Materials:</b>	Meets Guidelines
<b>LEED EQ4.3 Certified Low Emitting Product:</b>	Meets Guidelines
<b>LEED EQ4.1 Certified Low Emitting Adhesive:</b>	Meets Guidelines
<b>Passes NBS Smoke Density:</b>	Yes
<b>Passes Critical Radiant Flux (ASTM E-648 &gt; 0.45w/cm<sup>2</sup>):</b>	Yes
<b>Meets or Exceeds FHA / HUD Minimum Property Standards:</b>	Yes
<b>Slip Resistance:</b>	Meets ADA Recommendations
<b>Width:</b>	6 and 12 Feet
<b>Packaging:</b>	40-130 S.Y. (6') and 80-170 S.Y. (12')
<b>Shipping Weight per Unit:</b>	2.9 lbs. per S.Y.
<b>Shipping Weight per Package:</b>	230 lbs. avg. (6') and 460 lbs. avg. (12')
<b>Warranty Coverage:</b>	ArmorCore 5 Year Residential Limited Warranty Plus 5 year No Buckle warranty
<b>Installation Method:</b>	Your Choice Plus Fully Adhere, Perimeter Fasten or Loose Lay over Approved Wood, Concrete and Qualifying Existing Resilient Floors
<b>Subfloor Application:</b>	All grade levels
<b>Adhesive:</b>	UnderFlor® AS01 Adhesive or QS120 QuikStik Tape
<b>Porous and Non-Porous Surfaces:</b>	Applicator: ¼" Nap Paint Roller
<b>Adhesive Coverage:</b>	300 to 350 sq. ft. per gallon
<b>Optional Fully Adhere Application</b>	
<b>Porous Surfaces Only:</b>	Trowel Size: 1/16" wide, 1/32" deep, 1/32" apart
<b>Adhesive Coverage:</b>	200 to 250 sq. ft. per gallon
<b>Seam Sealer:</b>	Congoleum SU80 or SU92
<b>Suggested Usage:</b>	
<b>Residential:</b>	Excellent

**Finished product manufactured in the United States.**