



**PRODUCT:**

**Construction:**            **Wear Surface:**

**DURACERAMIC DIMENSIONS**

Nano-composite surface glaze, reinforced with Nylon particles and Aluminum Oxide featuring Scotchgard™ Protector

**Base:**

Limestone composite

**Nominal Overall Gauge:**

0.160" (4.1 mm)

**Nominal Size:**

12" x 24"

**Packaging:**

20 Sq. Ft. per Carton

**Pieces per Carton:**

10

**Shipping Weight per Package:**

36 lbs. per Carton

**Passes NBS Smoke Density:**

Yes

**Passes Critical Radiant Flux  
(ASTM E-648 > 0.45w/cm<sup>2</sup>):**

Yes

**Passes Motor Vehicle FMVSS 302:**

Yes

**PEI Rating:**

3-4

**Static Load Limit:**

250 psi

**Slip Resistance:**

Meets ADA Recommendations

**FloorScore Certified:**

Yes

**Warranty Coverage:**

Lifelong Residential

**Additional Scotchgard™ Protector**

**Will be easy to clean**

15 Years

**Will repel dirt and grime**

15 Years

5 Year Light Commercial

**Installation Method:**

Fully Adhered or Floating Installation over UnderFlor or QuikStik UnderFlor in residential application only

**Subfloor Application:**

On, above or below grade level

**Adhesive:**

UnderFlor® DS100 pressure-sensitive adhesive

**Adhesive Coverage:**

**Fully Adhered:**

200 to 250 sq. ft. per gallon

**Recommended Trowel:**

1/16" wide x 1/32" deep x 1/32" apart, trowel blade adapter included

**Grout:**

UnderFlor® Premixed sanded acrylic grout

**Grout Joint Width and Spread Ratio:**

1/16" - 450 sq. ft. per gallon

1/8" - 325 sq. ft. per gallon

3/16" - 275 sq. ft. per gallon

1/4" - 225 sq. ft. per gallon

**Suggested Usage:**

**Light Commercial**

Yes

**Private Residential**

Yes

**Finished product manufactured in the United States**