



<b>PRODUCT:</b>	<b>DURACERAMIC ORIGINS</b>
<b>Construction:</b>	<b>Wear Surface:</b> Nano-composite Surface glaze fortified with Aluminum Oxide featuring Silver Antibacterial Product Protection and Scotchgard™ Protector
	<b>Base:</b> Limestone composite
<b>Nominal Overall Gauge:</b>	0.160" (4.1 mm)
<b>Nominal Size:</b>	15 5/8" x 15 5/8" (40cm x 40cm)
<b>Packaging:</b>	17 Sq. Ft. (1.58 m <sup>2</sup> ) per Carton
<b>Pieces per Carton:</b>	10
<b>Shipping Weight per Package:</b>	30.5 lbs. per Carton
<b>Passes NBS Smoke Density:</b>	Yes
<b>Passes Critical Radiant Flux (ASTM E-648&gt;0.45w/cm<sup>2</sup>):</b>	Yes
<b>Passes Motor Vehicle FMVSS 302:</b>	Yes
<b>PEI Rating:</b>	3-4
<b>Static Load Limit:</b>	250 psi
<b>Slip Resistance:</b>	Meets ADA Recommendations
<b>FloorScore Certified:</b>	Yes
<b>Warranty Coverage:</b>	Lifelong Residential
<b>Additional Scotchgard™ Protector</b>	
<b>Will be easy to clean</b>	15 Years
<b>Will repel dirt and grime</b>	15 Years
	5 Year Light Commercial
<b>Installation Method:</b>	Fully Adhered or Floating Installation over UnderFlor or QuikStik UnderFlor in residential application only
<b>Subfloor Application:</b>	On, above or below grade level
<b>Adhesive:</b>	Congoleum DS-100 DuraSet Adhesive
<b>Adhesive Coverage:</b>	
<b>Fully Adhered:</b>	200 to 250 sq. ft. per gallon
<b>Recommended Trowel:</b>	1/16" wide x 1/32" deep x 1/32" apart
<b>Grout:</b>	Congoleum Premium Premixed Grout
<b>Grout Joint Width and Spread Ratio:</b>	1/16" - 450 sq. ft. per gallon 1/8" - 325 sq. ft. per gallon 3/16" - 275 sq. ft. per gallon 1/4" - 225 sq. ft. per gallon
<b>Suggested Usage:</b>	
<b>Light Commercial</b>	Yes
<b>Private Residential</b>	Yes

**Finished product manufactured in the United States**