



PRODUCT:	Ovations Luxury Tile
Construction: Wear Surface:	Satin Gloss with Aluminum Oxide
Base:	Limestone composite
Nominal Overall Gauge:	0.140" (3.5 mm)
Nominal Size:	14" x 14" (35.56 cm x 35.56 cm)
Packaging:	20.4 Sq. Ft. per Carton
Pieces per Carton:	15
Shipping Weight per Package:	32.7 lbs. per Carton
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648 > 0.45w/cm²):	Yes
Static Load:	250 psi
Slip Resistance:	Meets ADA Recommendations
FloorScore Certified:	Yes
Warranty Coverage:	20 Years Limited Warranty
Installation Method:	Fully Adhered or Floating Installation over UnderFlor or QuikStik UnderFlor
Subfloor Application:	On, above or below grade level
Adhesive:	UnderFlor [®] AD32 pressure-sensitive adhesive UnderFlor [®] DS100 pressure-sensitive adhesive
Spread Rate Fully adhered:	200 to 250 sq. ft. per gallon
Recommended Trowel:	1/16" wide x 1/32" deep x 1/32" apart, trowel blade adapter included
Grout:	UnderFlor [®] Premixed sanded acrylic grout
Grout Joint Width and Spread Ratio:	1/16" - 450 sq. ft. per gallon 1/8" - 325 sq. ft. per gallon 3/16" - 275 sq. ft. per gallon 1/4" - 225 sq. ft. per gallon
Suggested Usage:	
Public Commercial:	Not Recommended
Light Commercial:	Not Recommended
Private Residential:	Excellent

Finished product manufactured in the United States