



PRODUCT:	DURACERAMIC ORIGINS
Construction:	Wear Surface: Nano-composite surface glaze, reinforced with Nylon particles and Aluminum Oxide featuring Scotchgard™ Protector
	Base: Limestone composite
Nominal Overall Gauge:	0.160" (4.1 mm)
Nominal Size:	15 5/8" x 15 5/8" (40cm x 40cm)
Packaging:	17 Sq. Ft. (1.58 m ²) per Carton
Pieces per Carton:	10
Shipping Weight per Package:	30.5 lbs. per Carton
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648>0.45w/cm²):	Yes
Passes Motor Vehicle FMVSS 302:	Yes
PEI Rating:	3-4
Static Load Limit:	250 psi
Slip Resistance:	Meets ADA Recommendations
FloorScore Certified:	Yes
Warranty Coverage:	Lifelong Residential
Additional Scotchgard™ Protector	
Will be easy to clean	15 Years
Will repel dirt and grime	15 Years
	5 Year Light Commercial
Installation Method:	Fully Adhered or Floating Installation over UnderFlor in residential application only
Subfloor Application:	On, above or below grade level
Adhesive:	UnderFlor® DS100 pressure-sensitive adhesive
Adhesive Coverage:	
Fully Adhered:	200 to 250 sq. ft. per gallon
Recommended Trowel:	1/16" wide x 1/32" deep x 1/32" apart Trowel blade adapter included
Grout:	UnderFlor® Premixed sanded acrylic grout
Grout Joint Width and Spread Ratio:	1/16" - 450 sq. ft. per gallon 1/8" - 325 sq. ft. per gallon 3/16" - 275 sq. ft. per gallon 1/4" - 225 sq. ft. per gallon
Suggested Usage:	
Light Commercial	Yes
Private Residential	Yes

Finished product manufactured in the United States