

**PRODUCT:****Construction:** **Wear Surface:****Base:****Nominal Overall Gauge:****Nominal Size:****Packaging:****Pieces per Carton:****Shipping Weight per Package:****Passes NBS Smoke Density:****Passes Critical Radiant Flux
(ASTM E-648 > 0.45w/cm²):****Passes Motor Vehicle FMVSS 302:****PEI Rating:****Static Load Limit:****Slip Resistance:****FloorScore Certified:****Warranty Coverage:****Additional Scotchgard™ Protector****Will be easy to clean****Will repel dirt and grime****Installation Method:****Subfloor Application:****Adhesive:****Adhesive Coverage:****Fully Adhered:****Recommended Trowel:****Grout:****Grout Joint Width and Spread Ratio:****Suggested Usage:****Light Commercial****Private Residential****DURACERAMIC DIMENSIONS**

Nano-composite surface glaze, reinforced with Nylon particles and Aluminum Oxide featuring Scotchgard™ Protector

Limestone composite

0.160" (4.1 mm)

12" x 24"

20 Sq. Ft. per Carton

10

36 lbs. per Carton

Yes

Yes

Yes

3-4

250 psi

Meets ADA Recommendations

Yes

Lifelong Residential

15 Years

15 Years

5 Year Light Commercial

Fully Adhered or Floating Installation over UnderFlor in residential application only

On, above or below grade level

UnderFlor® DS100 pressure-sensitive adhesive

200 to 250 sq. ft. per gallon

1/16" wide x 1/32" deep x 1/32" apart
Trowel blade adapter included

UnderFlor® Premixed sanded acrylic grout

1/16" - 450 sq. ft. per gallon

1/8" - 325 sq. ft. per gallon

3/16" - 275 sq. ft. per gallon

1/4" - 225 sq. ft. per gallon

Yes

Yes

Finished product manufactured in the United States