



<b>PRODUCT:</b>	<b>Ovations Luxury Tile</b>
<b>Construction: Wear Surface:</b>	Satin Gloss Urethane with Aluminum Oxide
<b>Base:</b>	Limestone composite
<b>Nominal Overall Gauge:</b>	0.140" (3.5 mm)
<b>Nominal Size:</b>	14" x 14" (35.56 cm x 35.56 cm)
<b>Packaging:</b>	20.4 Sq. Ft. per Carton
<b>Pieces per Carton:</b>	15
<b>Shipping Weight per Package:</b>	32.7 lbs. per Carton
<b>Passes NBS Smoke Density:</b>	Yes
<b>Passes Critical Radiant Flux (ASTM E-648&gt;0.45w/cm<sup>2</sup>):</b>	Yes
<b>Static Load:</b>	250 psi
<b>Slip Resistance:</b>	Meets ADA Recommendations
<b>FloorScore Certified:</b>	Yes
<b>Warranty Coverage:</b>	20 Years Limited Warranty
<b>Installation Method:</b>	Fully Adhered or Floating Installation over UnderFlor
<b>Subfloor Application:</b>	On, above or below grade level
<b>Adhesive:</b>	UnderFlor <sup>®</sup> AD32 pressure-sensitive adhesive UnderFlor <sup>®</sup> DS100 pressure-sensitive adhesive
<b>Spread Rate Fully adhered:</b>	200 to 250 sq. ft. per gallon
<b>Recommended Trowel:</b>	1/16" wide x 1/32" deep x 1/32" apart Trowel blade adapter included
<b>Grout:</b>	UnderFlor <sup>®</sup> Premixed sanded acrylic grout
<b>Grout Joint Width and Spread Ratio:</b>	1/16" - 450 sq. ft. per gallon 1/8" - 325 sq. ft. per gallon 3/16" - 275 sq. ft. per gallon 1/4" - 225 sq. ft. per gallon
<b>Suggested Usage:</b>	
<b>Private Residential:</b>	Excellent
<b>Light Commercial:</b>	Not Recommended
<b>Public Commercial:</b>	Not Recommended

**Finished product manufactured in the United States**