

UNDERflor[®] ACOUSTIC UNDERLAYMENT



For Luxury Vinyl Tile, Laminate, Resilient & Wood Floors

UnderFlor[®] Acoustic Underlayment is a premium, high-density underlayment that suppresses noise and enhances the floor's comfort underfoot.

SUPERIOR PERFORMANCE

- **Reduces impact noise**
 - Deadens sound
- **High density**
 - Handles heavy impact loads
 - Holds up to extra-heavy foot and rolling wheel traffic
- **Features antimicrobial protection**
 - Inhibits growth of mold, mildew, and odor-causing bacteria
- **Installation advantage**
 - Fast and easy
 - Masks minor subfloor irregularities
 - Use over radiant heated floors
- **CRI Green Label Plus certification**
 - Contributes to good indoor air quality
- **Made in USA with global materials**

FOR USE UNDER...

- Luxury vinyl tile/plank
- WPC or SPC tile/plank
- Other premium resilient flooring
- Laminate or engineered hardwood
- Solid hardwood

Installation instructions can be found at www.congoleum.com/installation-brochures

Allows for floating (single-glue) systems with flooring >3.2 mm thick and for double-glue systems with flooring > 2 mm thick.

SPECIFICATIONS

Product Code: UFAU1

Composition: High-density synthetic rubber

100% resistant to topical liquids and spills*

Density: 64.5 lbs/ft³

Thickness: 0.06" (1.62 mm)

R-Value: 0.08

Color: Black

Castor Durability Test: Passes 25,000 cycles**

Pill Test (DOC-FF 1-70): Pass

Smoke Chamber: Pass

Dimensions: 54" x 44.44'

Ft²/Roll: 200

Yd²/Roll: 22.22

Roll Weight: 65 lbs.

* Separate vapor barrier should be used on slab foundation and below-grade installation

** Passes Castor Durability Test for 25,000 cycles when tested under minimum of 3 mm double-glued luxury vinyl plank and minimum 3.2 mm floating-click

ACOUSTICAL PERFORMANCE (Over 6" concrete with drop ceiling)

INSTALLATION	FLOORING	THICKNESS	IIC (NO UNDERLAYMENT)	IIC (WITH UNDERLAYMENT)	STC
GLUEDOWN	LVT TILE	4 mm	52	64	61
GLUEDOWN	LVT PLANK	2 mm	54	63	61
GLUEDOWN	LVT PLANK	3 mm	49	63	61
GLUEDOWN	CLEO™	4 mm	56	64	62
FLOATING	RIGID CORE	4.5 mm	53	67	62

Contact your local Congoleum distributor for more information or call 609-584-3000